



VRA Specifications

Convenient On-Site Fueling Systems
 for fleets, vehicles, forklifts & ice resurfacers.

Model	Max Discharge Pressure Psi	Hourly Flow Rate gge	Flow Rate scfm	Gas Inlet Pressure psi
FMQ-10	3,000	3.9	8.0	1 to 1 ¼+
FMQ8-36	3,600	3.7	7.6	1 to 1 ¼+
FMQ2-36	3,600	0.9	1.9	¼+
FMQ2	3,000	0.9	2.0	¼+

FMQ-10, FMQ-8-36



Big Q

Electrical

Electrical Supply	240 Volts AC, Single Phase, 60 Hz
Full Load Amperage	28 Amps
Average Power Consumption during fill	4.0 to 4.8 kWh
Required Distance from Storage	15 ft.
Classification	General Purpose

Mechanical

Dimensions (LxWxH)	33x48x32+
Unit Weight	580 lbs
Ambient Temperature Rating	-40 to +113 F
Service Interval	4,000 Hrs. (prior to 2012)
Noise Level	66 dBa @ 16.5 ft.

FMQ-2-36, FMQ-2



Small Q

Electrical

Electrical Supply	240 Volts AC, Single Phase, 60 Hz
Full Load Amperage	7 Amps
Average Power Consumption during fill	1.0 to 1.2 kWh
Classification	General Purpose

Mechanical

Dimensions (LxWxH)	21x20x39+
Unit Weight	145 lbs.
Ambient Temperature Rating	-40 to +113 F
Service Interval	4,000 Hrs. (prior to 2012)
Required Distance From Storage	15 ft.
Noise Level	49 dBa @ 16.5 ft.

For more information visit your local authorized dealer website or:
www.brcfuelmaker.it
www.impcotechnologies.com

Certifications



Authorized Distributor for Arizona & New Mexico



480-461-5166

www.cngaz.com

ROC231066